



United Process Valves

Tradition

Innovation

Commitment

ID & IP Series

IN-LINE DISC & PISTON VALVES





HISTORY & MILESTONES





IN-LINE DISC & PISTON VALVES

Code: IPYM

M Seal In-Line Piston Valve

Large valves utilize a non-rising stem to minimize overall length

Live loaded packing arrangement is standard

Jacket connections (oil or steam can be customized to the actual valve position

Optional heat jacketing

M Seal provides high sealing performance for high temperature. Other sealing systems are available




Fig. 038D

Code: IDYM

In-Line Disc Valve

Large valves utilize a non-rising stem to minimize overall length

Disc completely retracts into valve body to provide full flow

Seat position in body is optimized to minimize pressure drop and eliminate retention areas

Optional heat jacketing

Jacket connections (oil or steam) can be customized to the actual valve position




Fig. 050D



As an alternative to a failing ball, plug or gate valve, United Process Valves offers in-line disc and piston valves. With a wide range of positive sealing systems like M Seal, M Ring Seal and M Control, these valves provide superior in-line tightness. When opening the piston or disc it retracts completely into the valve body providing an unrestricted full flow. In combination with our maximized port sizes, these designs offer maximum flow capacity. They are available in a wide choice of options including materials of construction, sealing systems to atmosphere, actuators, full jacketing and a vacuum package. Typical applications for in-line piston valves is to provide a dead space free valve for high viscosity products or abrasive slurries, especially in combination with high pressures and high temperatures.

BODY ARRANGEMENTS

United Process Valves In-Line valves has several styles available:

- Figure 037 for small sizes Y pattern piston valves with a rising stem design
- Figure 038 for large sizes Y pattern piston valves with a non-rising stems
- Figure 050 for Y pattern disc valves with rising or non-rising stem
- Figure 055 for angle pattern disc valves with rising or non-rising stem




Fig. 037




Fig. 038




Fig. 050





Fig. 055



ADDITIONAL DRAIN OR INJECTION VALVE

In some processes, an additional valve can be required to serve as a drain valve for the product line (dump valve) or to inject additives. This additional valve can be welded to the body of the main valve as shown in this example.




RANGE DEFINITION



Available Sealing systems

M Seal offers a wide range of material combinations selected to create a differential hardness between body and plunger seat. The maintenance friendly design of the M Seal system provides long & reliable valve sealing performance and is suitable for almost all process conditions.




Temperature

Min: -200°C / -330°F
Max: 815°C / 1500°F

Pressure

Max: 630 bar / 9137 psi & full vacuum.

The M Ring Seal is also based on a differential hardness between the body and the piston surface. The replaceable metallic seal ring made of aluminum, nickel or titanium provides excellent sealing performance especially in applications that combine full vacuum and temperatures above 200°C.




Temperature

Min: -200°C / -330°F
Max: 450°C / 842°F

Pressure

Max: 250 bar / 3626 psi & full vacuum.

Dual Seal is a unique double sealing system that works like a piston operating within a cylindrical seat. Unlike other designs, the secondary resilient seal ring is mounted on the piston and will expand after metal to metal contact of the primary seat ring. The design provides a true metal to metal seal in case of resilient seat failure.



Temperature


Min: -50°C / -60°F
Max: 225°C / 437°F

Pressure

Max: 250 bar / 3626 psi & full vacuum.

M-Control provides customized flow characteristics to regulate a specific laminar flow with high viscosity. The system uses a piston with a specific shape to control flow and/or pressure. M-Control uses the specific sealing features of the M seal system.

Body cavity is sized to keep full flow capacity through the valve



Temperature


Min: -200°C / -330°F
Max: 815°C / 1500°F

Pressure

Max: 630 bar / 9137 psi & full vacuum.

Sealing system In-Line Disc Valves

M Seal offers a wide range of material combinations selected to create a differential hardness between body and plunger seat. The maintenance friendly design of the M Seal system provides long & reliable valve sealing performance and is suitable for almost all process conditions.



Temperature

Min: -200°C / -330°F
Max: 815°C / 1500°F

Pressure

Max: 630 bar / 9137 psi & full vacuum.




PACKING DEFINITION

Typical Packing Materials:


- PTFE
- PTFE / Aramide Braid
- Carbon / Graphite Braid
- Graphite Braid
- PTFE / Aramide Braid + Graphite
- Lamellar + Expanded Graphite
- Pure Graphite

Back seat arrangement is standard on this valve



VACUUM HOOD


For valves on full vacuum service United Process Valves offers a special **vacuum package** that maintains tightness to atmosphere. Valves with this package are usually equipped with an **M Ring Seal** design as process sealing. The system uses a replaceable aluminium or nickel seal ring and provides high vacuum performance. This special **vacuum package** provides zero leakage between atmosphere and process.



STANDARD BODY GASKET RANGE

- PTFE
- Aramide / Nitrile
- Carbon / Aramide
- Laminated Graphite
- Laminated Graphite / 316
- Spiral Wound 316L / PTFE
- Spiral Wound 316L / Graphite
- Spiral Wound 321 / Graphite
- Spiral Wound Inconel / Graphite
- Spiral Wound Titanium / Graphite
- Welded Lips

JACKET CONNECTIONS




Flanges
ANSI,DIN,JIS

Butt Weld

Socket
Weld, NPT

Threaded
connections
NPT & BSP

Valve Coding System





TECHNICAL & GENERAL INFORMATION

Design Code & Construction

- Design standard compliant with ASME B16.34
- International standards include ANSI, DIN, JIS, API etc.
- Wide range of material selections including carbon steel / stainless steel / Titanium / Hastelloy / Duplex / Monel / Tantalum / Zirconium
- Fabricated, cast, forged and bar stock designs
- Combinations of fabricated, sand and investment casings, and bar stock available

Surface Finish

- For polymer applications, United Process Valves recommends a surface facing of 300 (Ra 0.4) for all parts are in contact with the medium

Quality assurance & testing

- ISO 9001 compliant
- PED / ATEX / CE marking
- ISO 15848 1 & 2, low emission testing and certification available
- Standard testing procedures

LINE & BRANCH CONNECTIONS




Flanges
ANSI, DIN, JIS



Heated
Flanges




Socket
Weld



Threaded
connections
NPT & BSP



Butt
Weld



Fast Bolting Union
Graylock Securamax

ACTUATION OPTIONS




Hand Wheel



Bevel Gear



Electric Actuator




Air Motor



Double or single
acting Air Cylinder



Double or single acting Air
Cylinder with Safety Hand Wheel



Double or single acting Air
Cylinder with side mounted
Safety Hand Wheel



Hydraulic
Cylinder



United Process Valves products include:

PISTON TYPE SAMPLING VALVES

United Process Valves has a full line of sampling valves that produce live samples without exception. Our sampling valves unique design prevents failure caused by sediment or clogging.

PISTON TYPE DRAIN VALVES

United Process Valves Drain Valves are designed to prevent clogging. They are ideal for use in liquid and gas services or with slurries, polymers, and high viscosity fluids that tend to solidify at room temperature.

PISTON & DISC TYPE IN-LINE VALVES

United Process Valves Piston and Disc Type In-Line Valves alternative to a failing ball, plug or gate valve. With a wide range of positive sealing systems like M Seal, M Ring Seal and M Control, these valves provide superior in-line tightness. When opening the piston or disc it retracts completely into the valve body providing an unrestricted full flow.

PISTON & DISC TYPE DIVERTER VALVES

United Process Valves Diverter Valves are designed to divert process flows with high and low viscosity. They are dead space free to prevent clogging. They are ideal for use in liquid and gas services or with slurries, polymers, and high viscosity fluids that tend to solidify at room temperature.

SINGLE- & DOUBLE-DISC SLAB GATE VALVES

United Process Valves Single- & Double-Disc Slab Gate Valves are specifically designed for use in transfer line and decoking valves for ethylene cracking units and isolation applications in FCCU (fluid catalytic cracking unit) and DCU (delayed Coker unit) plants. The safety and continuous production of process plants often depend on the reliability of these "key-equipment" valves.

LINE BLINDS

United Process Valves Line Blinds provide zero leakage downstream and total isolation on process pipelines, vessels, and maritime applications. No pipeline movement is required when blind position is changed. Please contact your local United Process Valves representative for further details or visit our website:

www.unitedprocessvalves.com

United Process Valves, France

136 rue Sommeiller, ZA Savoie Hexapole
F-73420, Mery, France
Tel: + 33 4 79 35 78 00
E-mail: upvsales@upvalves.com

United Process Valves, German Office

Allerheiligenstrasse 69
D-77855 Achern, Germany
Tel: +49 (0) 170 9766629

United Process Valves, Shanghai China Office

Tel: +86 189 1751 7369

